




LUBRICANTS FOR HYUNDAI PASSENGER CARS



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for Hyundai.

Product name	Description	Specifications	Approvals	FUCHS Recommendations
Engine Oils				
TITAN SUPERSYN F ECO-B SAE 5W-20	Ultra High Performance, extreme fuel-economy engine oil especially developed for Ford EcoBoost gasoline engines. Optimum cold starting and lower oil consumption.	ACEA C5 API SN	–	–
TITAN GT1 FLEX C2 SAE 0W-30 	Premium Performance engine oil for modern cars and vans. Especially developed for BMW and Mercedes-Benz vehicles with exhaust gas aftertreatment and turbochargers, incl. hybrid vehicles. Excellent Cold-Start properties, low oil consumption and reduced emissions.	ACEA C2 ACEA A5/B5 API SP API SP RC	–	–
TITAN GT1 FLEX C23 SAE 5W-30 	Premium Performance, extreme fuel-economy engine oil with optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals. Additionally applicable in hybrid vehicles of different manufacturers.	ACEA C2/C3 API SP	–	–
TITAN SUPERSYN F ECO-DT SAE 5W-30	Ultra High Performance, extreme fuel-economy engine oil especially suitable for Ford DuraTorq-Diesel engines. Optimum cold starting and lower oil consumption.	ACEA A5/B5 API SL	–	ACEA A1/B1 API CF
TITAN SYN MC SAE 10W-40	Ultra High Performance, fuel-economy engine oil based on MC-synthesis for a variety of gasoline and diesel engines in passenger cars. Lower oil consumption.	ACEA A3/B4 API SN	–	API CF
Gear Oils				
TITAN SINTOFLUID SAE 75W-80	Premium Performance Manual Transmission Fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-4	–	–
Automatic Transmission Fluids (ATF)				
TITAN ATF 8400 ULV	Premium Performance ATF with extremely reduced viscosity specifically formulated for automatic transmissions of Japanese manufacturers. Product dyeing: red.	–	–	AISIN WARNER AW-2 DEXRON ULV
TITAN ATF 6400 	Premium Performance ATF with reduced viscosity specifically formulated for automatic transmissions of Japanese and American manufacturers. Licensed according to DEXRON VI and MERCON LV. Additionally also suitable for use in hybrid applications from various manufacturers. Product dyeing: red.	–	DEXRON VI	AISIN WARNER/AW-1 JWS 3324
TITAN ATF 4400	Ultra High Performance ATF specifically formulated for Japanese passenger cars and light commercial vehicles, as well as for several European and American manufacturers. The high torque capacity exceeds the performance of many original fluids. Product dyeing: red.	–	–	DEXRON III HYUNDAI SP III JWS 3309/TYP T-IV
Continuously Variable Transmission Fluids (CVTF)				
TITAN CVTF FLEX	Premium Performance CVTF specially designed for use in many CVT-gearboxes using push-belts or transmission chains made of steel. Product dyeing: none.	–	–	HYUNDAI/KIA SP-CVT1

LUBRICANTS FOR HYUNDAI PASSENGER CARS



Product name	Description	Specifications	Approvals	FUCHS Recommendations
Central Hydraulic / Power Steering Fluids				
TITAN CHF 202 	Premium Performance Power Steering and Central Hydraulic Fluid with a wide application and approval profile for various manufacturers. Product dyeing: green.	–	HYUNDAI 00232-19017	–
Antifreeze				
MAINTAIN FRICOFIN LL	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites, amines, phosphates and silicates with OAT-technology. Product dyeing: orange.	ASTM D 3306 TYPE I ASTM D 6210 TYPE I-FF BS 6580:2010 SAE J814	–	ASTM D 4985 SAE J1034 HYUNDAI MS 591-08
Brake Fluids				
MAINTAIN DOT 514 LV 	Premium Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 3/4/5.1 ISO 4925 CLASS 3/4/5-1/6/7 JIS K2233 CLASS 3/4/5/6 SAE J 1703/1704	–	–
<p>The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH. © FUCHS LUBRICANTS GERMANY GmbH. All Rights reserved. Issue 12/2022</p>				
FUCHS LUBRICANTS GERMANY GmbH Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719 E-Mail: export-flg@fuchs.com • www.fuchs.com/de/en			PARTNER des deutschen Kraftfahrzeuggewerbes	