







Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for Iveco.

Product name	Description	Specifications	Approvals	FUCHS Recommendations
<b>Engine Oils</b>				
<b>TITAN CARGO MAXX II SAE 5W-30</b> 	Premium MAXX Performance Engine Oil with new XTL-Technology. Specially developed for vehicles with modern exhaust after treatment and turbocharger. Optimum cold starting properties and ageing stability for extreme fuel-economy over the whole drain-interval.	ACEA E11, E9, E8, E7, E6, E4 API CK-4/CJ-4	–	IVECO 18-1804 CLASSE TLS E6
<b>TITAN CARGO MAXX II SAE 10W-40</b> 	Premium MAXX Performance Engine Oil with new XTL-Technology. Specially developed for vehicles with modern exhaust after treatment and turbocharger. Good cold starting properties and ageing stability for fuel-economy over the whole drain-interval.	ACEA E11, E9, E8, E7, E6, E4 API CK-4/CJ-4	–	IVECO 18-1804 CLASSE TLS E9 IVECO 18-1809 CLASSE NG2
<b>TITAN CARGO SL SAE 5W-30</b>	Premium Performance, extreme fuel-economy engine oil for a variety of commercial vehicle diesel engines, with optimum cold starting and lower oil consumption. Specially developed for extended service intervals.	ACEA E7, E4	–	IVECO 18-1804 CLASSE TFE
<b>TITAN TRUCK PLUS SAE 15W-40</b>	Ultra High Performance Engine Oil for a variety of diesel and gasoline engines. Specially for highly-loaded commercial vehicle diesel engines. Lower oil consumption.	ACEA E7 API CI-4/SL	–	IVECO 18-1804 CLASSE T2 E7
<b>Gear Oils</b>				
<b>TITAN CYTRAC TD SAE 75W-90</b>	Premium Performance Gear Oil for highly-stressed manual transmissions and hypoid axles in commercial vehicles formulated with fully-synthetic base oils. Developed for the longest oil change intervals.	API GL-4/GL-5 API MT-1 SAE J2360	ZF TE-ML 02B, 05A, 12L, 12N, 16F, 17B, 19C, 21A (ZF003341)	–
<b>TITAN CYTRAC ULTRA SYNTH SAE 75W-80</b>	Premium Performance Gear Oil for gear boxes in commercial vehicles, especially developed for ZF heavy duty transmissions with and without Intarder. Reduces fuel consumption by improving gearbox efficiency. Suitable for longest oil change intervals.	API GL-4	ZF TE-ML 01E, 02E, 16P (ZF008388)	IVECO 18-1807 MSG2
<b>TITAN CYTRAC MAT SAE 75W-80</b>	Premium Performance Gear Oil for gear boxes in commercial vehicles, specially developed for manual and automatic ZF-gear boxes, formulated with selected base oils. Reduces fuel consumption by improving gearbox efficiency. Suitable for the longest oil change intervals and compatible with Carbon-Synchronizers.	API GL-4	ZF TE-ML 01L, 02L, 16K (ZF003373)	IVECO 18-1807 CLASSE MGS1 ZF TE-ML 01E, 02D, 02E, 08, 16P
<b>TITAN SUPERGEAR MC SAE 80W-90</b>	Ultra High Performance Gear Oil based on MC-Synthesis for extended oil change intervals.	API GL-4/GL-5	ZF TE-ML 02B, 05A, 12L, 12M, 16B, 17H, 19B, 21A (ZF000722)	ZF TE-ML 07, 08
<b>TITAN SUPERGEAR MC SAE 80W-140</b>	Ultra High Performance Gear Oil based on MC-Synthesis for extended oil change intervals.	API GL-4/GL-5	ZF TE-ML 05A, 12M, 16C, 21A (ZF006028)	ZF TE-ML 08
<b>Automatic Transmission Fluids (ATF)</b>				
<b>TITAN ATF 5668</b>	Premium Performance ATF especially developed for highly stressed ALLISON step automatic transmissions in commercial vehicles. Product dyeing: red.	–	ALLISON TES 668®	ALLISON TES 295 ALLISON TES 389

Product name	Description	Specifications	Approvals	FUCHS Recommendations
<b>TITAN ATF 5500</b>	Premium Performance ATF for automatic transmission in motor vehicles. Outstanding base oil quality for optimal cold temperature properties and high ageing stability. Durable friction properties for excellent wet clutch performance. Product dyeing: none.	–	ZF TE-ML 04D, 14C, 16M, 16S, 20C, 25C (ZF001797)	DEXRON III (H) ALLISON TES 295 ALLISON TES 389 IVECO 18-1807 CLASSE AG3/I
<b>TITAN ATF 4000</b>	Ultra High Performance ATF for use in automatic transmissions as well as other ATF applications. Licensed according to DEXRON III (H). Improved low-temperature shifting compared to DEXRON II. Product dyeing: red.	–	DEXRON III (H) ZF TE-ML 04D, 14A (ZF000728)	ALLISON C-4 ALLISON TES 389 ZF TE-ML 02F, 03D, 09, 11B, 17C
<b>Central Hydraulic / Power Steering Fluids</b>				
<b>TITAN CHF 11S</b>	Premium Performance Power Steering and Central Hydraulic Fluid with a wide application and approval profile for various manufacturers. Product dyeing: green.	–	ZF TE-ML 02K (ZF004744)	IVECO 18-1807 CLASSE APU
<b>Antifreeze</b>				
<b>MAINTAIN FRICOFIN DP</b> 	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites, amines and phosphates with Si-OAT-technology. Product dyeing: pink-violet.	ASTM D 3306 TYPE I ASTM D 4985	–	IVECO 18-1830
<b>Brake Fluids</b>				
<b>MAINTAIN DOT 514 LV</b> 	Premium Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 3/4/5.1 ISO 4925 CLASS 3/4/5-1/6/7 JIS K2233 CLASS 3/4/5/6 SAE J 1703/1704	–	–

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH. © FUCHS LUBRICANTS GERMANY GmbH. All Rights reserved. Issue 12/2022

FUCHS LUBRICANTS GERMANY GmbH  
Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany  
Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719  
E-Mail: export-flg@fuchs.com • www.fuchs.com/de/en

**PARTNER**  
des deutschen Kraftfahrzeuggewerbes

