**Superior Motorcycle Oils** 

and Maintenance Products

### **MAINTAIN**

### Pro SRG 75 **SAE 75 FULLY SYNTHETIC**

- racing gear oil.
- crankcase rating SAE 10W-30.



# 80W-90

 extreme pressure gear oil Metric V-Twins.



### **Specifications:** API GL-5

 crankcase rating SAE 10W-40.

# **Gear Oil**

- Classic ST30
- Classic ST90

**Gear Oil** 

### outstanding lubrication & performance in transmission drive systems of scooters & mopeds.

# **V-Twin**

# **SEMI SYNTHETIC**

for Harley Davidson and



mp Gear 80W-90		SEMI SYNTHETIC racing gear oil.
	•	crankcase rating
		SAE 10W-40.

- hypoid gear oil.
- API GL5 SAE 80W-90.
- **Specifications:** motorcycle applications API GL-3 or API GL-4
- Specifications motorcycle applications
- API GL-3 or API GL-4 crankcase rating SAE 20W-50.
- non EP Gear oil **Specifications:** Meets API GL-3 formulated especially for
- classic Vespa gearboxes.
- non EP Gear oil Specifications: formulated especially for Meets API GL-3 classic Lambretta gearboxes.
  - Specifications: Meets API GL-4

Specifications:

## **MAINTAIN**

grades can be mixed.

Suspension fluids, coolants, fuel additives

A race/road/track proven suspension fluid already in use and chosen by many of today's market leading suspension manufacturer's.

### **ISO 22 RSF 7.5**

ISO 32 **RSF 10** 

**RSF 2.5** 

**ISO 15** 

RSF 5

### **ISO 46 RSF 15 ISO 100**

SF20 **ISO 68 SF30** 

**ISO 100** 

- · high VI index monograde formulation, combats friction, protects seals and resists
- ensures smooth suspension under all road and competition conditions grades can be mixed.
- 02 Synthetic
- exceptional performance and zero drag Fork Oil in racing forks. ISO 15/22 low friction synthetic additives ensure
- smooth, predictable action on all terrains. 05 Synthetic Fork Oil
  - reduces stick-slip, minimises pressurisation at high temperature in all conditions.
- **Mag Cool**

**ISO 46** 

 ready to use premium coolant based on mono-ethylene glycol.

free from nitrites, amines, silicates and phosphates

race proven.

non-toxic.

- advanced all-season pre-mixed engine coolant **Pro Cool** based on mono-propylene glycol.
- advanced multi-functional fuel treatment. Pro FST
  - protects against cold start wear, corrosion, carburettor icing, deposit build up problems, and rough running at low engine revs.
- **Pro Boost**
- octane improver added to petrol will also have a 'keep clean effect' in both carburettor and injection systems and will help to reduce icing in carburettors. Fully compatible with all petrols and does
- **Pro CCA** 
  - race engine corrosion inhibitor.
    - mixing ratio 3% to 5%. Does not protect from frost.

not attack fuel hoses or filters.

### **MAINTAIN**

Brake & clutch fluids, cleaners, grease

### Universal **Brake &** Clutch fluid

- suitable for UK, US, European and Japanese motorcycles.
- Mixes safely with all fluids meeting the standards FMVSS116 DOT 5.1, DOT 4 and DOT 3, ISO 4925
- Typical dry boiling point 230°C (446°F)
- Typical wet boiling point 155°C (311°F)

### **Pro Race Brake Fluid**

- high quality Racing Brake Fluid suitable for race or road use. SPECIFICATION: DOT 4
- Typical dry boiling point 315°C (594°F)
- Mixes safely with all fluids meeting the standards FMVSS116 DOT 5.1, DOT 4 and DOT 3, ISO 4925 • Typical wet boiling point 204°C (399°F)
- **Foam Filter**

Cleaner

 a highly effective, water rinsable cleaner/ degreaser formulated specifically for cleaning foam filters prior to re-oiling.

Minimum wet boiling point 195°C (383°F)

- Foam Filter
- advanced, low viscosity coating treatment designed to improve the efficiency of foam air filters.
- contains polymeric additives to provide a hyper-tacky surface that resists the ingress of elements without affecting engine breathing.

### **Foam Filter** Oil Kit

The kit contains buckets x2, gloves, strainer, 1x 4L SILKOLENE FOAM FILTER CLEANER 1x 1L SILKOLENE FOAM FILTER OIL.

a complete system for foam filter cleaning.

## Wash Off

 a cost-effective spray-on / hose-off bike cleaner suitable for all street and off-road motorbikes, bicycles, guads and ATV's.

### Copper **Paste**

- superior high temperature anti-seize lubricant containing copper.
- designed to control pitting, rusting, thread distortion and seizure due to corrosion. Reduces dismantling torque.

### an advanced, high melting point, Pro /RG2 **Grease**

- synthetic racing grease. multi-functional, with exceptional heat
- resisting & water-proofing properties. outstanding water repellence and corrosion inhibition properties. SPECIFICATION: NLGI-2

### **MAINTAIN 500ml AEROSOLS**

Chain Lube	semi-Synthetic chain oil suitable for road and off-road use.
Pro Chain	100% Synthetic Racing chain oil, suitable for road & off road use.      **Silkotent***  Chain Euler**  **Tracket**  *
Titanium Dry Lube	non fling PTFE boosted chain lube, with exceptional anti-wear and anti-corrosion performance.
Pro Prep	<ul> <li>high quality water repellent, hard surface conditioner which gives that elusive 'factory finish.</li> </ul>
Brake & Chain Cleaner	<ul> <li>a powerful cleaner - perfect for removing unwanted deposits.</li> </ul>
Contact Cleaner	<ul> <li>a powerful solvent cleaner ideal for cleaning electrical components.</li> </ul>
Injector & Carb Cleaner	<ul> <li>removes internal and external gum from carburettors and injection systems.</li> </ul>
All in One	<ul> <li>premium, multi-purpose, moisture repellent spray for use in the garage and home.</li> </ul>
Silkopen	<ul> <li>graphited penetrating spray to ease the dismantling of seized threaded fastners.</li> </ul>
Foam Filter Oil	<ul> <li>advanced low viscosity coating treatment.</li> <li>Improves the efficiency of foam air filters.</li> </ul>

### **CLASSIC OILS**

hatsworth 30	<ul> <li>monograde low deterger</li> </ul>
SAE 30	/dispersant engine oil.

### Chatsworth 40 **SAE 40**

- monograde non-detergent engine
   API SA Donington 40 oil. Suitable for certain 1930s & **SAE 40** 1940s vintage & veteran motorcycles.
- Hardwick 50 monograde, detergent/dispersant engine oil. Includes high levels of anti-wear additives. monograde non-detergent engine API SB **Osmaston 50** oil. Can also be used for total loss **SAE 50 lubrication systems & certain** gearboxes.
- Multipurpose mild EP gear oil. Suitable API GL3 Rhino 140 for use in gearboxes and final drives where this type of oil is specified. multigrade low detergent/dispersant
   API
- Silkolube engine oil. Suitable for many pre SF/CC 20W-50 1990s classic motorcycles. monograde non-detergent engine oil.

  API SA Straight 30 Suitable for pre 1930s motorcycles.
- SAE 30 2T Pre-Mix

**SAE 40** 

 synthetic ester 2-stroke oil. Suitable
 APLTC for older pre-mix engines and certain rotary engines.

JASO FB

f /fuchslubricantsuk @fuchs\_silkolene

in /fuchs-lubricants-uk-plc

Dealer:

### FUCHS LUBRICANTS (UK) plc New Century Street, Hanley, Stoke on Trent, Staffordshire, ST1 5HU, England. Phone: +44 (0)1782 203 700 E-mail: contact-uk@fuchs.com www.silkolene.com // www.fuchs.com/uk





All information correct at time of publication. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS. © FUCHS LUBRICANTS. All rights reserved.

The birth in 1908 of the innovative company that was later to become

Manufactured in Stoke-on-Trent, FUCHS Silkolene is now a truly global

brand sold in over 50 countries with over 30 years R&D expertise. Our

products are used, approved and demanded by leading professional race teams including MotoGP, World Superbikes, British Superbikes,

Developed using the latest lubricant technologies our products offer

Over the last few years our products have developed into the most

reduced oil consumption, improved API specs and enhanced BHP

comprehensive 100% dedicated Motorcycle range. The development

of our Market leading **XP Technology**, offers increased fuel economy,

XP uses the latest technology,

**FUCHS SILKOLENE** can offer:

which means that only

users measurable performance improvements.

across the Pro 4 and Comp 4 range.

TECHNOLOGY

of Belper, Derbyshire, England

Motocross, Speedway and Karting.

known as "Silkolene" was the vision of the entrepreneurial Dalton family

5W-40

**Ouad ATV** 

**PRO** Ester Based Fully Synthetic

### Pro 4 XP

5W-40 / 10W-30 / 10W-40 10W-50 10W-60 / 15W-50

- formulated to meet the needs of both air and watercooled 4-stroke engines.
- the recommended SAE grades for the majority of motorcycle manufacturers.



full oil service life

**Specifications:** API SN JASO MA2 APPROVED

increased power and optimum

stay-in-grade capability ensures

consistent performance for the

engine protection over a wide

range of ambient temperatures.

Specifications: API SN. ACEA A3/B3 JASO MA2 APPROVED



### **COMP** Ester Based Premium Semi Synthetic

Comp 4 XP

10W-30 / 10W-40 15W-50 / 20W-50

- formulated to meet the needs of both air and watercooled 4-stroke engines.
- the recommended SAE grades for the majority of motorcycle manufacturers.

**V-Twin** 20W-50

- mineral engine oil for all Harley Davidson and Metric V-Twins.
- provides high level of engine
- protects engine components from wear and corrosion.



**Specifications:** API SL Specifications: API SL JASO MA2 APPROVED JASO MA2 APPROVED

### **Ouad ATV** 10W-40

anti-wear detergents, dispersants, and anti-corrosion systems provide excellent engine cleanliness and minimum wear to ensure long-term reliability.

### **Scoot Sport 4** 5W-40

latest technology provides increased power and optimum engine protection for improved long term performance and reliability.



Specifications: API SL JASO MA2 APPROVED



**Specifications:** API SN JASO MA2 APPROVED

### **SUPER** Semi Synthetic

Scoot 4

conditions.

provides exceptional

anti-corrosion and anti-wear

performance, even under

ideal for use in all modern

high performance, free

revving 4 stroke scooters.

extreme temperature

10W-30 /10W-40 / 20W-50

10W-30 MP / 10W-40

 protects the engine and transmission with advanced additive chemistry from start to full power.

Super 4

 detergents, dispersants & load carrying agents give excellent engine cleanliness & minimum wear of moving parts.



Specifications: API SL JASO MA2 APPROVED

Specifications: API SL JASO MA2 APPROVED

### **PRO** Fully Synthetic: **RACE application** Pro 4 Plus • Ultimate fully synthetic ester engine oil. Proven formula increases power, gives ultimate performance and reliability. SPECIFICATION: API SL, JASO MA2 Unique low viscosity synthetic which cuts oil drag yet maintains a tough low-wear film on highly stressed components. SPECIFICATION: FOR Castorene • Castor & Synthetic ester blend - suitable for 2T & 4T engines. For dry sump speedway engines. Recommended for use in both air & liquid cooled racing engines especially

competition oil which can

provide the latest racing

engines with outstanding

load-carrying and cleanliness

requirements necessary for

full power output even at

high fuel to oil ratios.

Only for use with PreMix

**PRO** Ester Based Fully Synthetic

Pro 2







 compatible with all fuels. Consult recommendations.

systems. Recommended mix up to

50:1 (2%). **DO NOT MIX** WITH CONVENTIONAL OILS.

Specifications: CIK FIA HOMOLOGATED

### Comp 2 Plus

- Injector systems.

API TC. ISO L-EGD. JASO FC/FD.

**COMP** Ester Based Premium Semi Synthetic

### Comp 2

- advanced low smoke. low ash formula reduces engine wear - prevents piston seizure, & exhaust port blockage.
- refer to handbook for mix recommendations. Compatible with all fuels.

Specifications: API TC. ISO L-EGD JASO FC/FD.

- for high output kart engines giving exceptional performance and reliability
- engine manufacturer for mix DO NOT MIX WITH OTHER LUBRICANTS.

Specifications: CIK FIA HOMOLOGATED

**SUPER** 

Semi Synthetic

clean burning formula

reduces wear and ensures

does not contain spirit or

suitable for Pre-Mix and

Injector systems. Compatible

Specifications: APLTC / JASO FC /

kerosene dilutents.

with all fuels.

ISO-L-EGC

Super 2

reliability.

- ultra low smoke, clean burning lubricant providing maximum performance, extra power and reliability
- compatible with all fuels
- suitable for pre-mix and

Specifications:

- suitable for pre-mix and Injector systems. Mix well.

Selected products available currently in 4L & 20L Scan this code to watch the Lube Cube Story...

Leading the way in lubricant

innovative packaging solution

packaging with our

GO GREEN and help reduce

100%\*

\*Wash plastic inner prior to disposal

Environmentally friendly Zero waste & spills

Easy to use / Easy to store

Recyclable

Packaging

the Lube Cube.

plastic pollution.

<sup>s</sup> Silkolene

Pro 4 10W-40

### **Classic 2 Stroke**

- fully Synthetic ester, clean burning, low smoke formula.
- reduces friction and wear.
- maintains optimum power and is fully compatible with all modern fuel.

Specifications: API TC. ISO L-EGD. JASO FC/FD.

### Ester Based Premium Semi Synthetic

### **Scoot Sport 2**

- clean burning, low smoke engine oil. Optimises power and improves fuel economy
- outstanding resistance to ring sticking, plug fouling and pre-ignition.
- compatible with all fuels. Suitable for both premix and injector systems.

**Specifications:** API TC. ISO L-EGD JASO FC/FD.





Semi Synthetic

### Scoot 2

- MC-Syn Technology provides excellent anti-wear properties.
- a clean burning, low smoke
- compatible with all fuels.

Specifications: JASO FC / ISO-L-EGC



FIND THE RIGHT PRODUCT at silkolene.com FIND THE RIGHT PRODUCT at silkolene.com