

Alert Turbine Test

Within the scope of our service Lab Advisor Alert, we offer a complete analysis package for turbine oils. Alert Turbine Test is part of a systematic maintenance allowing you to quickly get an indication if something is not right in your system. It is easy to get started with Alert Turbine Test. Order a sampling kit where you order your other lubricant products.

It is easy to get started with Alert Turbine Test. Order a sampling kit where you order your other lubricant products. The first time you use Alert you register the system you wish to send samples from and then you can easily print labels via our website. After about a week, you receive the analysis report via e-mail and in addition you have access to all previous reports on our website.

Order

- Box with 3 sample bottles, item number 940052350
- For questions please contact your sales representative

Below you will find an overview of the analyzes included in Alert Turbine Test.

Test	Method	Turbine B
Air Release @ 50°C	ASTM D3427	X
Appearance	In-house	X
Water Separation @ 54°C	ASTM D 1401	X
Ferrous Debris by PQ Particle Quantifier	In-house	X
Foaming Characteristics @ 24° C (Seq I)	IP146	X
ISO Particle Counting*	ISO 4406	X
Kinematic Viscosity @ 40 and 100°C*	ASTM D 7279	X
Rotating Pressure Vessel Oxidation Test (RPVOT)	ASTM D 2272	X
RULER	ASTM D6971	X
Rust Prevention	IP135A	X
Neutralization number*	IP 139/ASTM D 974	X
Varnish Potential by MPC	ASTM D 7843-12	X
Water Content by Karl Fischer*	ASTM D 6304	X
Wear Metals And Contamination Elements by ICP*	ASTM D5185	X

*Accredited to UKAS ISO 17025