

## **High-Tech Protection for Engines.**



		Specifications	Approvals	Recommendations
GT1 EVO 0W-20 XTL	Designed for highly stressed downsized engines with maximum power output.	ACEA A1/B1	BMW LONGLIFE-14 FE+ JAGUAR LAND ROVER STJLR.51.5122	-
GT1 PRO V 0W-20 XTL	Designed for modern VOLVO vehicles.	ACEA A1/B1	VOLVO VCC RBS0-2AE	-
GT1 LONGLIFE IV SAE 0W-20	Designed for modern VW vehicles for extreme fuel-economy characteristics.	ACEA A1/B1	VW 508 00/509 00	PORSCHE C20
GT1 LL-12 FE SAE 0W-20 XTL	Specially developed for latest BMW gasoline and diesel vehicles.	ACEA C2	BMW LONGLIFE-12 FE	-
GT1 SAE 0W-30	For modern passenger cars and light commercial vehicles.	ACEA C2	PSA B71 2312	FIAT 9.55535-DS1/GS1 IVECO 18-1811 CLASSE SC1 LV
GT1 PRO FLEX SAE 5W-30	Specially developed for BMW, Mercedes-Benz and Opel vehicles.	ACEA C3; API SN/SM	BMW LONGLIFE-04 dexos2 <sup>™</sup> (GB2C0209075), MB 229.51/ 229.52, VW 502 00/505 00/505 01	FIAT 9.55535-S3; GM-LL-A-025; GM-LL-B-025
GT1 PRO C-3 SAE 5W-30	Specially developed for BMW, VW and Mercedes-Benz vehicles.	ACEA C3; API SN	BMW LONGLIFE-04, MB 229.51, PORSCHE C30, VW 504 00/ 507 00	FIAT 9.55535-S3
GT1 PRO 229.6 SAE 5W-30	Designed for modern Mercedes-Benz gasoline vehicles.	ACEA A5/B5	MB 229.6	-
GT1 PRO C-1 5W-30	For modern passenger cars and light commercial vehicles.	ACEA C1	JAGUAR LAND ROVER STJLR.03.5005	JASO DL-1 FORD WSS-M2C934-B
GT1 PRO C-2 5W-30	For modern passenger cars and light commercial vehicle	ACEA C2; API SN/SM	PSA B71 2290	API CF FIAT 9.55535-S1 IVECO 18-18111 CLASSE SC1 PSA B71 2290
GT1 PRO C-4 5W-30	For modern passenger cars and light commercial vehicle	ACEA C4	MB 226.51, RENAULT RN0720	-
GT1 5W-40	For modern passenger cars and light commercial vehicle	ACEA C3; API SN/SM FORD M2C917-A	BMW LONGLIFE-04; PORSCHE A40 dexos2™ (D20311HE075) MB 226.5/229.31, RENAULT RN0700/RN0710, VW 502 00/ 505 00/505 01	API CF; FIAT 9.55535-S2
SUPERSYN LONGLIFE PLUS 0W-30	Developed for VW LONGLIFE technology for all passenger car engines.	-	VW 503 00/506 00/506 01	ACEA A5/B5 BMW LONGLIFE 01-FE
SUPERSYN LONGLIFE 0W-30	High performance, extreme fuel-economy engine oil for a variety of vehicles.	ACEA A3/B4 API SL	MB 229.5, VW 502 00/505 00	BMW LONGLIFE-01
SUPERSYN LONGLIFE 0W-40	High performance, extreme fuel-economy engine oil for a variety of vehicles.	ACEA A3/B4 API SN	BMW LONGLIFE-01 MB 229.5, PORSCHE A40; VW 502 00/505 00	FORD M2C937-A
SUPERSYN LONGLIFE 5W-40	High performance, extreme fuel-economy engine oil for a variety of vehicles.	ACEA A3/B4; API SN/SM	BMW LONGLIFE-01, MB 226.5/ 229.5, PORSCHE A40, PSA B71 2296, RENAULT RN0700/ RN0710, VW 502 00/505 00	API CF; GM-LL-B-025
SUPERSYN FE 0W-30	For a variety of vehicles with or without extended service intervals.	ACEA A5/B5	VOLVO VCC 95200377	RENAULT RN0700
SUPERSYN G 5W-30	Especially developed for OPEL/GM extended service intervals.	ACEA A3/B4; API SL/CF	-	GM-LL-A-025 GM-LL-B-025
SUPERSYN F ECO-FE 0W-30	Especially developed for modern Ford Diesel engines.	ACEA C2; FORD M2C950-A	-	-
SUPERSYN F ECO-B 5W-20	Especially developed for Ford EcoBoost gasoline engines.	ACEA C5; API SN FORD M2C948-B	JAGUAR LAND ROVER STJLR.03.5004	ACEA A1/B1, CHRYSLER MS 6395, FORD M2C925-A / M2C925-B
SUPERSYN F ECO-DT 5W-30	Suitable for Ford DuraTorq-Diesel engines.	ACEA A1/B1/A5/B5; API SL; FORD M2C913-C; M2C913-D	Jaguar Land Rover Stjlr.03.5003	API CF; CHRYSLER MS 6395; FORD M2C913-A/M2C913-B; IVECO 18-1811 CLASSE S1/S2; JAGUAR M2C913-B RENAULT RN0700
SUPERSYN D1 5W-30	Especially suitable for GM gasoline engines requiring dexos1TM - Gen 2 fluid.	api SN-RC Ilsac GF-5	dexos1™ - Gen 2 (D10173GJ075)	FORD WSS-M2C929-A FORD WSS-M2C946-A FIAT 9.55535-CR1 CHRYSLER MS 6395 GM 6094M; GM 4718M
SUPERSYN 5W-40	For a variety of vehicles with or without extended service intervals.	ACEA A3/B4; API SN/SM	MB 229.3, PORSCHE A40 RENAULT RN0700/RN0710 VW 502 00/505 00	API CF; BMW LONGLIFE-98 FIAT 9.55535-H2/M2/N2/Z2 GM-LL-A-025; GM-LL-B-025
SYN MC 10W-40	Based on MC-synthesis for a variety of engines in passenger cars.	ACEA A3/B4; API SN	MB 229.1 / 229.3, PSA B71 2300, RENAULT RN0700 / RN0710, VW 502 00/505 00	API CF FIAT 9.55535-D2/G2



## Tried and tested on the track.



		Specifications	Recommendations
<b>ENGINE OILS</b>			
TITAN RACE PRO S RANGE			
5W-30 5W-40 10W-50 10W-60	Full synthetic, high performance engine oil providing optimum protection for extended engine life and reliability. Suitable for use in petrol engines to ensure continued maximum fuel economy and reduced emissions.	API SN, SM, SL API SN, SM, SL API SL, SJ, SH API SL, SJ, SH	BMW MERCEDES
TITAN RACE PRO R RANGE			
10W-40 15W-50 20W-50	High performance engine oil providing outstanding protection for highly stressed engines. Suitable for use in petrol engines to ensure continued maximum fuel economy and reduced emissions. Benefits all high performance power units running on lead free, low-lead or racing gasolines.	API SL, SJ, SH API SL, SJ, SH API SL, SJ, SH	-
TITAN RACE PRO C-3 5W-30	Designed to be used in modern high performance road cars which are also used on track. Suitable for use in petrol and diesel engines and is compatible with emission reduction systems where an oil of ACEA C3 performance level is specified.	-	ACEA C3 BMW MERCEDES PORSCHE VAG GROUP
TITAN RACE PRO R 0W-20	A unique low viscosity synthetic lubricant which cuts oil drag yet maintains a tough low-wear film on highly stressed components. Some older engine designs may have inadequate oil pump capacity under race conditions to maintain full oil pressure with this low viscosity product. This product is strictly for professional racing & track use.	-	-
GEAR OILS			
COMP GEAR	A high performance synthetic ester based gearbox oil designed primarily for off-road by reducing viscous drag & friction. COMP GEAR ensures slick gear changes. Also suitable for road going sports machines where the gearbox and clutch lubrication is combined.	-	·
SRG 75	A full ester synthetic SAE 75 gear oil with naturally high viscosity index ensuring good low and high temperature performance. Possesses excellent shear strength and carrying capability.	-	r
GEAR 90LS	A high performance mineral based gear oil for hypoid and spiral bevel axles, which has excellent extreme pressure, anti-corrosion, anti-oxidation and anti-foam properties. This unique formula contains friction modifiers designed to make GEAR 90LS ideal for limited slip differentials operating under severe conditions including competition use.	Recommended for use with the following specifications: API GL5	API GL6 PERFORMANCE
SYNCHRO SAE 75W-90	Designed for use in manual transmissions operating under arduous and high speed applications where an oil of this viscosity and performance level is specified. Especially recommended for road going track cars with manual transmissions including synchromesh gearboxes.	Recommended for use with the following specifications: SAE 75W-90, API GL-4	Manual transmissions Synchromesh gearboxes
SYN 5 SAE 75W-90	Highest quality fully synthetic; PAO/Ester based multifunctional gear lubricant for use in manual transmissions and final drives where an SAE 75W-90, API GL-5 gear oil is recommended. Designed for use in dog/crash boxes, sequential gearboxes and final drives working in severe applications.  Especially recommended for race applications.	Recommended for use with the following specifications: SAE 75W-90, API GL-5	Not recommended for synchromesh transmissions
SINTOFLUID SAE 75W-80	Premium gear oil offering good gearbox efficiency. Suitable as fill for life fluid. Reliable operation under high loads in manual transmissions. Protects against wear, sludge formation, agglomeration and corrosion. Good viscosity temperature behaviour lying above the performance of many normal service gearbox lubricants.	API GL-5	MIL-L-2105 D, BMW 83 22 0 309 031 / 83 22 0 403 247 /83 22 2 339 219 83 22 7 533 818 / 2300 1434 404 2300 7533 513 / 2300 7533 818 FORD WSS-M2C200-C3 OPEL 19 40 182 / 19 40 757 VOLVO 97308 VW 501 50 (G 005 000 05/ G 005 000/G 005 000 20/ G 052 911 A1/A2)