

MAINTAIN FRICOFIN

Super High Performance coolant concentrate based on monoethylene glycol. Free from nitrite, amine and phosphate.

Description

MAINTAIN FRICOFIN is an antifreeze coolant concentrate based on mono ethylene glycol. It is free of nitrite, amine and phosphate. Due to its additive composition MAINTAIN FRICOFIN belongs to the hybrid type coolants. MAINTAIN FRICOFIN provides reliable protection against damages caused by cavitation, frost, corrosion and overheating for both modern passenger car and heavy duty engines. Due to its highly active component package, MAINTAIN FRICOFIN protects all metals used in coolant systems. At the same time it preserves seals, plastics and hoses.

Application

MAINTAIN FRICOFIN must be diluted with water, before filled into the coolant system. MAINTAIN FRICOFIN can be mixed with distilled or fully demineralised or tap water to a concentration range of 35% to 50% by volume. The analysis analytical properties of the water should not exceed the following limits.

Water hardness:	0 - 20 °dGH (0-3,6 mmol/l)
Chloride content:	max. 100 ppm
Sulphate content:	max. 100 ppm

Should analysis of water exceed these limits it can be easily adjusted by adding distilled or deionised water. Manufacturers drain intervals and recommendations about the application concentration are mandatory.

Attention:

This product is recommended for use at combustion engines only.

Advantages/Benefits

- Universal use in both passenger car and heavy duty engines, where a silicate containing coolant is recommended.
- Excellent for use in engines, cylinder heads and radiators made of alloy.
- Outstanding protection against deposits, cavitations and corrosion.
- Contains bittering agent

Specifications

- AFNOR NF R 15-601 TYPE 1
- AS/NZS 2108:2004 TYPE A
- ASTM D 3306 TYPE I
- ASTM D 4985
- BS 6580:2010
- CUNA NC 956-16
- SAE J814, SAE J1034

Approval

- BMW GS 94000
- (BMW N 600 69.0)
- CAT / MWM TR 0199-99-2091
- DEUTZ DQC CA-14
- GE JENBACHER TA 1000-0201
- MAN 324 TYPE NF
- MAN 324 TYPE NF PRITARDER
- MB-APPROVAL 325.0
- MTU MTL 5048
- PN-C 40007:2000
- VOITH TURBO 172.00225010

FUCHS Recommendations

- DAF 74001
- LIEBHERR TLV 035/TLV 23009 A
- OPEL/GM B 040 0240
- VW TL 774-C (G11)

MAINTAIN FRICOFIN

Super High Performance coolant concentrate based on monoethylene glycol. Free from nitrite, amine and phosphate.

TYPICAL CHARACTERISTICS

Density at 20 °C	DIN 51757	1.119 g/ml
Boiling point	ASTM D 1120	>165 °C
pH-value	DIN 51 369	7.2
Product dyeing	DIN 10964	blue green

mixing ratio

MAINTAIN FRICOFIN : H₂O

1:1 (50%)	-37°C / -34,6°F
2:3 (40%)	-25°C / -13°F
1:2 (33%)	-17°C / 1,4°F



MAINTAIN FRICOFIN

Super High Performance coolant concentrate based on monoethylene glycol. Free from nitrite, amine and phosphate.

The information contained in this brochure is based on the experience and know-how of FUCHS LUBRICANTS CO. in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc.

For this reason, universally-valid statements about the function of our products are not possible. The information given in this Product Information sheet represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application.

We therefore recommend you consult a FUCHS LUBRICANTS CO. Application Engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our Product Information sheets at any time and without warning. With the publication of this Product Information sheet, all previous editions cease to be valid.

ANY FORM OF REPRODUCTIONS REQUIRES EXPRESS PRIOR WRITTEN PERMISSION FROM FUCHS LUBRICANTS CO.

© FUCHS LUBRICANTS CO. All rights reserved.